



## **LensCoat® Nikon 500mm F/5.6E PF VR INSTRUCTIONS**

### ***Piece 1- Lens Hood Cover***

Remove the lens hood cover from the lens. Carefully slide and stretch the lens cover into hood.

Remove the tripod mount foot from the rotating lens collar it will allow for easy installation of pieces 2-5.

### ***Piece 2***

After removing the tripod mount foot, slide piece 2 down below the focus ring, tapered side towards the camera.

### ***Piece 3***

Slide piece 3 down to the focus ring.

### ***Piece 4- VR/AF Controls and Distance Scale Window***

Slide piece 4 on by **lining up the VR/AF controls and distance scale windows and slide into place being careful not to get the plastic windows caught on the rotating collar knob. For final placement pull the distance scale window slightly away from the lens and adjust to the left or right.**

**\*\*You should be able to slide the controls through the plastic window with your finger. Some people like to punch small holes in the plastic to allow for easier access. If you choose to do this, be careful, as it is easy to destroy the window.**

### ***Piece 5***

Slide on piece 5 by lining up the hole to the rotating collar adjustment and the cutout for the lens foot on the lens being careful not to pull/stretch the hole too much to prevent tears.

### ***Piece 6***

Slide on piece 6 by lining up the hole to the alignment dot on the lens being careful not to pull/stretch the hole too much to prevent tears.

LensCoat.com®  
80 Throckmorton Street  
Freehold, NJ 07728