



LensCoat® Nikon Z 400 f4.5 VR INSTRUCTIONS

Piece 1- Lens Hood Cover

Remove the lens hood cover from the lens. Piece 1 has a notch at one end of the cover which lines up with the hood release button. Carefully slide and stretch the lens cover into place.

Remove the tripod foot from the rotating lens collar. This will allow for easy installation of pieces 2-7.

Piece 2

After removing the tripod mount foot slide piece 2 down the lens to front of the lens, tapered side towards the camera. This section also covers the ring with the L-Fn buttons, these can be operated through the material

Piece 3 – control ring

Slide piece 3 down to the control ring.

Piece 4

Slide piece 4 on between the control ring and the focus wheel

Piece 5 – focus ring

Slide on piece 5 down to the focus ring

Piece 6

Carefully slide piece 6 down to behind the focus ring and in front of the lens collar

Piece 7 – lens collar

Slide piece 7 on to the lens collar. This section has an elastic which goes around the lens foot and a hole for the tension knob.

Piece 8

Slide on piece 8 at the rear of the lens by **carefully lining up the VR / Focus Preset window and slide into place being. For final placement pull the window slightly away from the lens and adjust to the left or right.**

****you should be able to slide the controls through the plastic window with your finger, some people like to punch small holes in the plastic to allow for easier access, if you choose to do this be careful as it is easy to destroy the window.**

LensCoat.com®
80 Throckmorton Street
Freehold, NJ 07728