



LensCoat® Sony FE 100-400mm f/4.5-5.6 GM OSS INSTRUCTIONS

Piece 1- Lens Hood Cover

Remove the lens hood cover from the lens. Carefully slide and stretch the lens cover into.

Remove the tripod mount foot from the rotating lens collar for easier placement of the sections.

Piece 2

After removing the tripod mount foot slide piece 2 down toward the end of the lens past the retracting barrel.

Piece 3

Slide piece 3 down onto the focus ring.

Piece 4

Slide piece 4 down between the zoom and focus ring

Piece 5

Slide piece 5 down onto the zoom ring

Piece 6

Slide piece 6 down onto the smooth/tighten ring.

Piece 7- Window piece

Slide piece 7 on by **carefully lining up the AF/OS window and slide into place. For final placement pull the distance scale window slightly away from the lens and adjust to the left or right. A small part of this piece needs to slide under the lens foot attachment part of the rotating collar.**

Piece 8

Slide piece 8 down to just before the rotating collar.

Piece 9

Slide piece 9 down onto the last section of the lens.

Rotating Lens Collar

The LensCoat® Sony 100-400 lens cover kit includes one strip of neoprene with adhesive tape applied to the back. Cut out the desired length for the parts of the lens collar you want to cover. Cut the longest piece first. After all the cutting is done then remove the adhesive tape backing by carefully folding back a small corner and apply to the lens collar.

Zoomed Lens Barrel

The LensCoat® Sony 100-400 lens cover kit includes an optional piece that can be affixed to the lens via the Velcro strip **ONLY** when the lens is fully extended

LensCoat.com®
80 Throckmorton Street
Freehold, NJ 07728