



LensCoat® Canon 100mm f2.8 L IS Macro INSTRUCTIONS

Piece 1- Lens Hood Cover

Remove the lens hood cover from the lens. Carefully slide and stretch the lens cover into place.

Piece 2

With the lens hood removed, stretch and slide piece 2 down from the glass to just above the focus ring lining up the distance scale window. **For final placement pull the window slightly away from the lens and adjust to the left or right.**

Piece 3

Slide on piece 3 to the focus ring.

Piece 4

Slide piece 4 over the lens and position it lining up the mount hole (red dot) and the control switch window. **For final placement pull the window slightly away from the lens and adjust to the left or right.**

****You should be able to slide the controls through the plastic window with your finger. Some people like to punch small holes in the plastic to allow for easier access. If you choose to do this be careful as it is easy to destroy the window**

Optional Rotating Lens Collar

The LensCoat® Canon 100mm f2.8 Macro L IS lens cover kit includes a smaller piece 4 for use when the Rotating lens collar is attached. Also a strip of neoprene with adhesive tape applied to the back for the rotating lens collar. Cutout the desired length for the parts of the lens collar you want to cover. Cut the longest piece first. After all the cutting is done then remove the adhesive tape backing by carefully folding back a small corner and apply to the lens collar

LensCoat.com®
80 Throckmorton Street
Freehold, NJ 07728