



LensCoat® Sigma 500mm DG OS HMS Sport INSTRUCTIONS

Piece 1- Lens Hood Cover

Remove the lens hood cover from the lens. Piece 1 has a ¼ inch hole at one end of the cover to accommodate for the lens hood locking knob. Carefully slide and stretch the lens cover into place without putting too much stress on the lock knob hole.

Remove the tripod mount foot from the rotating lens collar it will allow for easier installation of pieces 2-5.

Piece 2

After removing the tripod mount foot, slide piece 2 down below the focus ring, tapered side towards the camera.

Piece 3

Slide piece 3 down to the focus ring, tapered side towards the camera.

Piece 4- AF/OS Controls and Distance Scale Window

Slide piece 4 on by **carefully lining up the AF/OS controls and distance scale windows and slide into place being careful not to get the plastic windows caught on the rotating collar knob or strap attachment. For final placement pull the distance scale window slightly away from the lens and adjust to the left or right.**

****You should be able to slide the controls through the plastic window with your finger. Some people like to punch small holes in the plastic to allow for easier access. If you choose to do this, be careful, as it is easy to destroy the window.**

Piece 5

Slide piece 5 on by lining up the focus recall window and the hole for the filter knob. Carefully slide and stretch the lens cover into place without putting too much stress on the filter knob hole.

Rotating Lens Collar

The LensCoat® Sigma 500mm lens cover kit includes a strip of neoprene with adhesive tape applied to the back. Cut out the desired length for the parts of the lens collar you want to cover. Cut the longest piece first. After all the cutting is done then remove the adhesive tape backing by carefully folding back a small corner and apply to the lens collar.

LensCoat.com®
80 Throckmorton Street
Freehold, NJ 07728